



ND INDUSTRIES, INC.
 1893 BARRETT ROAD
 TROY, MICHIGAN 48084
 (248) 288-0000 Fax: (248) 288-0022
24 hr. EMERGENCY CHEMTREC:
1-800-424-9300

PRODUCT: ND Stay-Put™
MSDS ID: ND1021
ORIG. DATE: 3/23/93
REV. DATE: 1/30/06

PREPARED BY: Chemical Safety

SECTION I -Material Identification and Information H: 1 F: 1 R: 0 PPEB

COMPONENTS	CAS #	PERCENT %	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED
Polyamide resin	SP2-00-12	non-haz 99.0	n.a.	n.a.	

All ingredients are listed on the TSCA Inventory. n.a.= not applicable / n.e.=not established

SECTION II -Physical and Chemical Characteristics

BOILING POINT: Unknown. **VOC #/gal. :**

VAPOR DENSITY: n.a. air = 1 **DENSITY OF COATING:**

VAPOR PRESSURE: Not established

MELTING POINT: > 292.5°F

SPECIFIC GRAVITY: 1.006 water = 1

EVAPORATION RATE: n.a.

WATER REACTIVE: No.

SOLUBILITY IN WATER: Negligible.

APPEARANCE AND ODOR: Hazy amber solid with negligible odor.

SECTION III - Fire and Explosion Hazard Data

FLASH POINT: > 550°F Cleveland

AUTOIGNITION TEMPERATURE: n.a.

FLAMMABILITY LIMITS % IN AIR: LEL: n.a. UEL: n.a.

EXTINGUISHER MEDIA: Use CO2, foam or dry chemicals. Avoid using water.

SPECIAL FIREFIGHTING PROCEDURES: Wear NIOSH approved self-contained breathing apparatus operated in pressure-demand or other positive pressure mode when fighting fires. Cool fire exposed containers with water. Avoid using direct straight water stream on molten material to reduce spattering and spreading of fire.

UNUSUAL FIRE HAZARDS AND CONDITIONS TO AVOID: Potential toxic fumes upon combustion.

MATERIAL SAFETY DATA SHEET

PRODUCT: ND Stay-Put™

Component	Oral LD50	Dermal LD50	Inhalation LC50
Polyamide resin	not established	not established	not established

SECTION VI - Control and Protective Measures

RESPIRATORY PROTECTION: As supplied, not necessary.

PROTECTIVE GLOVES: Use vinyl or rubber gloves.

EYE PROTECTION: Wear NIOSH approved chemical splash goggles.

VENTILATION TO BE USED: LOCAL EXHAUST: MECHANICAL: SPECIFIC:
OTHER (specify): n.a.

PROTECTIVE CLOTHING AND EQUIPMENT: This product should only be heated to recommended temperatures.

HYGIENIC WORK PRACTICES: Always practice good personal hygiene when working with chemicals and wash hands after using product.

SECTION VII - Precautions for Safe Handling and Spill/Leak Procedures

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED:

Sweep up solid material and dispose of properly. Allow molten material to solidify, scrape up and dispose of properly.

WASTE DISPOSAL METHODS: Dispose of material in accordance with local, state and federal regulations.

SAFE HANDLING AND STORAGE: This product should only be heated to recommended temperatures.

OTHER PRECAUTIONS AND SPECIAL HAZARDOUS INFORMATION:
n.a.

RECOMMENDED NFPA/HMIS RATING

HEALTH 1

FLAMMABILITY 1

REACTIVITY 0

PERSONAL PROTECTION B

note: ratings may differ according to application, environment, and physical state.

MATERIAL SAFETY DATA SHEET

PRODUCT: ND Stay-Put™

NOTES:

Proper DOT Shipping Name:
Not Regulated

SECTION 313 SUPPLIER NOTIFICATION

Detaching this notification from the Material Safety Data Sheet is prohibited by law and any copying or distribution of same requires this attachment be included.

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372:

<u>CAS #</u>	<u>CHEMICAL NAME</u>	<u>% BY WEIGHT</u>
--------------	----------------------	--------------------

This product does not contain regulated levels of any toxic chemical subject to the reporting requirements of section 313 of Title III of the Superfund Amendments Reauthorization Act of 1986 (40 CFR 372)

This product contains the following materials that under California Proposition 65 of the Safe Drinking Water and Toxic Enforcement Act of 1986 are recognized to cause cancer or reproductive toxicity.

<u>Material</u>	<u>CAS #</u>	<u>Concentration %</u>	<u>Cancer Agent</u>	<u>Reproductive Toxin</u>	<u>cancer agent & Reproductive Toxin</u>
Arsenic compounds		0.0001	X		

ND Stay-Put™ is a trademark of ND Industries®, Inc.

The information contained herein is based on the data available to us and is believed to be correct. However, ND Industries®, Inc. makes no warranty, expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their properties prior to use. Since conditions of use are beyond our control, all risks are assumed by the user.